Magnetic and resonant properties of ferrite compositions (1-x)MeFe₂O₄:xP₂O₅

prepared by plasma spraying

A.A. Lepeshev^{a,b*}, I.V. Karpov^{a,c}, A.V. Uschakov^{a,c}, G.E. Nagibin^a

^a Siberian Federal University, Krasnoyarsk, 660041, Russia

^b Krasnoyarsk Scientific Center of the Siberian Branch of the Russian Academy of Science,

Krasnovarsk 660036, Russia

^c Reshetnev Siberian State Aerospace University, Krasnoyarsk 660037, Russia

* Corresponding author.

E-mail address: sfu-unesco@mail.ru (A.A. Lepeshev)

Abstract

It was found that after plasma spraying and rapid quenching of ferrite compositions (1-

x)MeFe₂O₄•xP₂O₅ within the range of 0.35<x<0.4 for any considered compounds, transition to

the X-ray-amorphous state is observed (so called concentration depended transition (CDT). This

transition occurs along with modification of X-ray and Mössbauer spectra (quadrupole splitting

into isomer shift) and changing their magnetic parameters: a saturation magnetization σ_s , a

coercive field H_c and a line width of ferromagnetic resonance (FMR) ΔH . The abnormal increase

of saturation magnetization σ_s is revealed at T < 100 K. Particularities of changing the Curie

temperature T_c and a saturation magnetization σ_s at different rates of quenching ferrites from the

liquid state are discussed.

Keywords: ferrites, plasma spraying, magnetic properties.

Highlights:

• We studied the influence of the ferrite compositions inclusion on their magnetic state;

• We studied the behavior of the magnetic parameters (T_c, σ_s, H_c) of spinel ferrites under

different conditions of rapid quenching;

• We studied the γ-spectra of ferrite compositions;

• We studied the behavior of the magnetic parameters H_c and ΔH at concentration

transitions (CDT).

1. Introduction

Magnetic ordering and corresponding magnetic properties of ferrites are significantly

determined by their structural condition and the distribution of cations on sublattice points.

1

Therefore, searching new ferromagnetic materials has been mainly carried out for the purpose of creating multi-component compounds with complex chemical composition [1-4]. This approach is aimed at the possibility of selective injection of various ions into the sublattice, with the consequent changes of the character and the ratio of intra- and inter-sublattice exchange interactions, and as a result, changes of the magnetic properties of these compounds. In this respect, the investigation was focused on defining of the composition – property regularities.

An alternative approach in the production of new materials appeared because of the possibility to influence the oxide compounds by concentrated energy flows (plasma, laser, etc.). This enables rapid heating and subsequent ultra-fast quenching of the melt [5-11]. After corresponding treatment, a number of changes are observed in the structure and properties of the substances. They are as follows: decrease of the crystallite size, increase of material disorder, increase of solubility limit for the components in multiphase systems, formation of metastable crystalline phases, redistribution of cations at sublattice points, as well as partial or complete amorphization of the compound. Due to strong correlation between the structural state, the type of spin ordering and the set of magnetic characteristics of the oxides, determining the correlation Structure – Disorder state – Property would provide direct control of the ferrite properties.

Compared to metal alloys, ferrites with spinel structure are prone to amorphization significantly less and are prone to thermal conductivity much less (by several orders). Therefore the production of iron oxides in the X-ray amorphous state is quite difficult because of achieving rather high rate of quenching the melt.

Widely known amorphizing additions such as B₂O₃, SiO₂, P₂O₅ and Bi₂O₃ can be used in some cases to facilitate the amorphization process [3]. The additives significantly reduce the critical rate of ferrite compositions quenching, and in most cases are not included in the ferrite composition.

The abovementioned approaches were used to achieve non-equilibrium state (up to amorphization) of ferrite compositions $(1-x)MeFe_2O_4 \cdot xP_2O_5$ during plasma spraying. [11,12]

This paper shows the results of new studies of the magnetic state, resonance and magnetic properties of ferrite compositions based on spinel ferrites.

2. Materials and Methods

The initial crystalline spinel ferrite powders $MeFe_2O_4$ (where Me is Fe, Ni, Co, etc.) were synthesized according to the traditional ceramic technology. The final sintering of ferrites was carried out in the opened air at the temperature of T = 1400 K during 4 hours followed by slow cooling.

The structural disordering of the prepared samples was carried out by means of:

- plasma spraying and subsequent rapid quenching of melt droplets in water and copper disc;
 - diluting the initial ferrite with amorphizing addition of P₂O₅.

Ferrite compositions (1-x)MeFe₂O₄•xP₂O₅ were prepared from the initial ferrites by adding a required amount of phosphorus pentoxide and sintering the mixture at the temperature T = 1100 K.

The plasma spraying of ferrite composite powders with a dispersion of $50 < d < 80 \,\mu m$ was carried out in the plasma of (Ar + CO₂) with the Ar/CO₂ ratio by volume equal to 1/3, at the arc discharge power, not exceeding 10 kW. Spraying was carried out by plasmatron with coaxial powder feed into the cathode zone [14]. The melt drops were quenched on the polished external surface of the fast-rotating copper disk ($\sim 12 \cdot 10^3$ rpm), placed in the reaction chamber. In order to avoid thermal exposure of the disk, the process nozzle was put on the plasmatron. In some cases, in order to avoid the dependence of material properties on the conditions of its preparing, the spraying process parameters remained constant.

The γ -resonance measurements were performed by the spectrometer MC 1104E with source of Co₅₇ in a chrome matrix. The spectra were recorded at room temperature (T = 22 °C) in a constant acceleration mode. The test samples were placed into containers made of a thin aluminum foil.

The resonant magnetic properties were investigated by means of the FMR spectrometer at 9.2 Hz frequency and the magnetic fields reaching 20 kOe. The magnetic measurements were performed by the magnetometer with a vibrating sample in the range of magnetic field of $-25 \div 25$ kOe.

The phase composition of the obtained samples was performed using Advance D8 X-ray diffractometer in CoKα monochromatic radiation.

3. Results and discussion

X-ray diffraction pattern of ferrite compositions has significantly changed after plasma spraying and quenching on the disk. Broadening and disappearance of sharp diffraction lines, characteristic of long-crystalline order, and emergence of clearly defined diffuse scattering, characteristic of the amorphous state, were observed.

Fig. 1 shows an example of such a change in the form of an X-ray image of quenched powder compositions based on cobalt ferrite (1-x)CoFe₂O₄•xP₂O₅. The diffraction pattern of the samples with a low content of P₂O₅ (about 10-35%) appears as a group of broadened reflexes

corresponding to a spinel structure. Since phosphorus-containing compounds are the first to become amorphous while quenching, samples are likely to have amorphocrystalline condition. The X-ray spectra of the ferrite compositions with P_2O_5 content exceeding 35%, do not exhibit Bragg reflections, which indicates the amorphous state of the samples.

Under the fixed quenching conditions, the minimum concentration of P_2O_5 at which a transition in the amorphous state is observed, reflects propensity of ferrite compositions to become amorphous. Ferrite components from the studied composition can be arranged in order of increasing propensity to amorphisation: $Fe_3O_4 < CoFe_2O_4 < Mn-Zn < Ni - Zn < NiFe_2O_4$.




Fig.1. X-ray of the quenched ferrite compositions (1-x)CoFe₂O₄•xP₂O₅. (a) initial, x=0.35; (b) quenched, x=0.35; (c) quenched, x=0.45

Let's discuss the results of the Mossbauer studies of ferrite powders quenched from a liquid state, showing change of their magnetic state [4, 17, 18]. Fig. 2 shows Mossbauer spectra of nickel ferrite samples (x = 0) in the initial state and after plasma spraying into water and on the disk surface.

Nickel ferrite has a structure of completely inverted spinel $Fe^{3+}[Ni^{2+} Fe^{5+}]O^4$. Nickel ions occupy octahedral positions and iron ions are distributed equally on the octahedral and tetrahedral positions. The lines of γ -spectrum are differentiated, that allow defining the state of the Fe^{3+} cations in octahedral and tetrahedral positions. The external lines correspond to the positions of the iron ions in octahedral positions, and the internal lines refer to the tetrahedral positions.

The Mössbauer spectra of nickel ferrite in the initial state is characterized by the symmetry of lateral lines, which indicates a uniform distribution of Fe^{3+} cations on the octahedral and tetrahedral positions (Fig. 2, a). Plasma spraying and quenching of ferrite results in some changes of the spectra, while the lines broadening is observed, and appearance of the doublet in the central part and the asymmetric distribution of the lateral lines pairs is viewed. The degree of these changes increases while the quenching rate is increased (Fig. 2, *b*, *c*).

The observed asymmetry of lateral lines proves the change in the distribution of Fe³⁺ ions on the sublattice points, therefore the relative amount of the cations in octahedral positions decreases. Probably the process goes with redistribution of Ni²⁺ ions in tetrahedral positions. The doublet in the central part of the spectrum seems to appear due to the formation of amorphous phase in the ferrite.

This indicates to the presence of iron ions both with the increased magnetic field compared to the initial one, and with hyperfine zero magnetic field. This case can occur because of a non-equilibrium distribution of cations, characterized by two states of iron ions: magnetically ordered and disordered, leading to both increasing and decreasing an exchange interaction degree.

We should also note that the amorphous state throughout the whole volume was not reached even at high quenching rates (on a copper disk) of molten droplets of ferrite spinels. This is also confirmed by electron beam diffuse scattering, characteristic to the amorphous state, which was observed only at the edges of the thinnest parts (~100 nm) of the flakes.

Let's consider the behavior of the γ -spectra of ferrite composition (1-x)NiFe₂O₄•xP₂O₅, containing various percentage of amorphizing addition P₂O₅. Mössbauer spectra of quenched nickel composition at low concentrations of P₂O₅ (x = 0.2) represents a superposition of the magnetic hyperfine structure, characteristic of a magnetically ordered state, and situated in the central part of the spectrum of the asymmetric doublet (Fig. 3). It should be noted, that the observed hyperfine structure is characterized by the same features (lateral lines and their asymmetry) as the original nickel ferrite.

Increasing the content of phosphorus pentoxide in the sample causes the broadening and decrease in the intensity of the lines, which are characteristic for hyperfine structure of the Mossbauer spectrum, until they completely disappear at the concentration depended transition (CDT) at x = 0.35. Simultaneously, an asymmetric triplet is formed in the central part of the spectrum. As a result, the spectra of the samples, being in the amorphous state (x = 0.4), represents the intensive triplet while a magnetically ordered phase is not indicated at all.

The appearance of the doublet in the central part of the Mossbauer spectrum is probably due to the formation of an amorphous phase, and the presence of some ions of Fe²⁺ and Fe³⁺ in it.

Since ferrites include at least two times more ferrous irons in comparison with the ferric ions, then the doublet, corresponding to Fe^{2+} ions, does not appear in the initial stages of amorphization. Increasing the percentage of the amorphous phase leads to the superposition of two doublets corresponding to Fe^{2+} and Fe^{3+} ions with different degree of the isomer shift and quadrupole splitting, and to formation of an intense triplet.

Corresponding changes of Mössbauer spectra are observed for other ferrite compositions. Table 1 shows the parameters of isomer shift, quadrupole splitting and the ratio of their areas corresponding to the ions of Fe²⁺ and Fe³⁺ in the amorphous state. It is obvious, that the amorphous compositions, in spite of the differences in the initial ferrites, are characterized by similar values of the Mössbauer parameters. This indicates that amorphized ferrite compositions have very similar magnetic states.

Table 1 - Basic parameters of the Mössbauer spectra of ferrite compositions 0.6MeFe₂O₄•0.4P₂O₅ at T = 300 K

Ме	Isomer shift, mm/s		Quadrupole splitting, mm/s		Ratio Fe ³⁺ /Fe ²⁺
	Fe ³⁺	Fe ²⁺	Fe ³⁺	Fe ²⁺	Ratio re /re
Fe	0.65	1.27	0.95	2.34	1.18
Co	0.71	1.29	0.99	2.4	1.15
Ni	0.67	1.24	0.97	2.33	1.06
Mn-Zn	0.7	1.28	0.98	2.37	1.22
Ni-Zn	0.66	1.22	1.00	2.41	1.19




Fig. 2. Mössbauer spectra of nickel ferrite: a - ferrite at the initial stage; b - ferrite after quenching on water; c - ferrite after quenching on the disk




Fig. 3. Mössbauer spectra of nickel composition (1-x)NiFe₂O₄•xP₂O₅ quenched on copper disk: a - x = 0.2; b - x = 0.35; c - x = 0.4

Let's analyze the magnetic properties of spinel ferrites in correlation with the quenching conditions after plasma spraying. Table 2 shows that the magnetic parameters (σ_s , T_c , H_c) mostly

change during spraying ferrites on a rotating disk. In this case (while spraying the substance on the disk), the highest rate of quenching is reached, and the highest structural disorder of ferrites is observed.

One of the particularities of the investigated ferrites (x=0), regardless of their chemical composition, was a sharp decrease in the saturation magnetization σ_S following a rapid quenching process (Fig. 2). Compared with the bulk polycrystalline ferrites, the range of σ_S change was more than 30%. It is hardly possible to explain the observed significant change of the resulting magnetization σ_S by non-equilibrium distribution of cations on sublattices. Evidently, rapid quenching of the melt results in the deformation of backbone oxygen atoms simultaneously with the redistribution of cations, which leads to changing the crystal fields symmetry, the value and the type of the exchange bonds under study.

Let's pay attention to the behavior of Curie temperature for the quenched ferrites of different composition. While MeFe₂O₄ compounds (where Me is a Fe, Ni, Co or Mn atoms) show decrease of T_c with increasing the quenching rate, then Ni-Zn and Mn-Zn ferrites are prone to greatly increase the Curie temperature.

The Curie temperature can be represented in the following generalized view according to the molecular field theory [15]:

$$T_{\rm c} = -\frac{2}{3}S(S+1)Z_{BA}J_{AB}^{eff}/K,\tag{1}$$

where J_{AB}^{eff} is an effective exchange integral measurable in Kelvin,

 Z_{BA} is a number of the nearest to A neighbors of Fe³⁺ ion.

It is known [12-14] that fast quenching of ferrites causes a formation of the amorphous-crystalline state with disordered micro-zones. The magnetic state of corresponding micro-zones considerably depends on their size. So, decrease of the disordered micro-zones causes increase of the percentage of magnetically active ions, located near the border and having less number of exchange couplings. These changes probably imply the Curie temperature decrease and the specific magnetization reduction.

The situation changes significantly when the initial ferrite contains diamagnetic ions in tetrahedral positions. In this case, ferrites quenching causes cations redistribution, and a certain amount of Fe^{3+} ions transfer into these tetrahedral positions. While the value of the exchange integral J_{AB} is considerably determined by strong A-B interaction of magnetically active Fe^{3+} ions and the number of interlattice exchange couplings of Fe^{3+} -O- Fe^{3+} increases, as a result, the increases of Curie temperature is observed.

Table 2 - Magnetic properties of ferrite powders after plasma treatment and quenching

Ferrite	Cooling conditions	σ_S , emu/g	H _c , Oe	T _c , K
Fe ₃ O ₄	а	82.3	43	858
	b	73.5	96	855
	c	52.2	185	808
	а	43.5	25	863
NiFe ₂ O ₄	b	39.0	75	859
	c	28.8	140	833
	а	71.6	315	793
CoFe ₂ O ₄	b	63.2	354	793
	c	47.9	578	768
	а	74.5	8	783
MnFe ₂ O ₄	b	64.3	27	780
	c	49.2	94	770
Ni-Zn	а	61.8	2	413
	b	50.4	24	453
ferrite (600 HH)	c	41.1	69	513
Mn-Zn	a	62.5	4	400
ferrite	b	58	23	426
TOTTIC	c	46	51	510

Notes. Quenching: a) in inert gas; b) in liquid nitrogen; c) on a rotating disk. Values σ_S and H_c are measured at the temperature of 300 K

As it could be expected, dilution of ferrites with phosphorous pentoxide resulted in further decrease of saturation magnetization σ_S . The specific features of temperature behavior of σ_S at the temperatures of T = 100 K and the Curie temperature of the amorphous samples T_c remained approximately the same as that of the initial stage ferrites. The abrupt increase in the magnetization at low temperatures should be referred to the magnetic properties changes for ferrite compositions. The abrupt changes of σ_S were observed in the temperature range of 4.2-80 K, and their intensity depended on the composition of the samples (Fig. 4).




Fig. 4. The temperature dependence of magnetization for ferrite compositions $0.6\text{MeFe}_2\text{O}_4 \cdot 0.4$ P₂O₅: (1) Me-Mn; (2) Me-Fe; (3) Me-Ni

The results of investigating the concentration dependence of a saturation magnetization σ_s , a coercive force H_c and a width of ferromagnetic resonance line ΔH are shown in Fig. 5,6. It is easy to notice, that H_c and ΔH correlate most strongly with the change in the structural state (the concentration depended transition (CDT) at x = 0.35).

The coercive force of nickel composition is reduced by nearly one order while the substance becomes X-ray-amorphous. In the concentration range of x < 0.35 the quenched samples possess disordered amorphous crystal microstructure and a high coercive force ($H_c \sim 250 \text{ Oe}$). In the X-ray-amorphous state at x > 0.35 the value of H_c is reduced down to 5 Oe, what indicates the presence of more homogeneous material structure. After annealing the sample at 973 K, the coercive force is reduced by approximately two times (at x < 0.35), but it remains sensitive to the concentration depended transition (CDT).

The measurement of the FMR line width ΔH was carried out on flakes with thickness of one micron order. As this value is significantly less than the depth of the skin layer, it can be assumed that the total volume of the sample undergo the resonance conditions. At the range of low concentrations of P_2O_5 , the width of FMR line was approximately equal to 0.9 kOe and correlates with ΔH value of the quenched nickel ferrite. While increasing the phosphorus pentoxide concentration, the width of FMR line is increased and reached its maximum at x = 0.35, and then decreased to the value of H = 1.24 kOe, when x = 0.6 (Fig. 6).




Fig. 5. Concentration dependence of the coercive force: 1 – samples at the initial stage; 2 – samples after annealing at 700 °C




Fig. 6.Ferromagnetic resonance line width and the saturation magnetization of the nickel compositions

As the width of the line is significantly determined by the local anisotropy of the material, the observed dependence of ΔH in the value interval of the CDT towards the amorphous state is

consequently explained. Indeed, the decrease in P_2O_5 percentage in the samples should cause the appearance and growth of crystal nuclei. Naturally, it causes various types of defects, inhomogeneities and other stresses, that finally determine the loss, and as a result, the increase of the FMR line width in the CDT interval.

It should be noted that the FMR line width in the amorphous state is more than that of the crystal one. Although it could seem to the viewer, that on the contrary, it should be reduced, while amorphous materials are isotropic. Most probably, the reason for this disagreement is the following: in spite of the integrated isotropic characteristics, amorphous materials possess a sufficiently large local anisotropy, which influences the FMR line width.

It has been shown that the saturation magnetization σ_S monotonically decreases while the persentage of P_2O_5 is increased in nickel composition. Therefore the saturation magnetization does not significantly change in the range of critical concentrations x = 0.35 - 0.37 (Fig. 6).

Conclusion

Structural features, magnetic and resonant properties of rapidly quenched ferrite compositions (1-x)MeFe₂O₄•xP₂O₅ (where Me is Fe, Co, Ni, Zn, Mn) were studied. It was shown that after plasma spraying and fast quenching of ferrites (x=0) a value of saturation magnetization σ_S considerably changes (> 30%). This effect can hardly be explained only by redistribution of Fe cations on sublattices. Dilution of ferrites with phosphorous pentoxide P₂O₅ resulted in further decrease of saturation magnetization σ_S . It was found that after plasma spraying and rapid quenching in the range of 0.35 < x < 0.4 a transition to the X-ray-amorphous state was observed for all the studied compositions. The concentration depended transition (CDT) is accompanied by modification of X-ray and Mössbauer (quadrupole splitting and isomeric shift) spectra and by the change in magnetic parameters: a coercive field value and a FMR line width. Configuration, size and number of exchange couplings changed because of the structural disorder. This leads to modification of spin ordering and changes in the fundamental magnetic characteristics of ferrites (σ_S , T_C , H_C , ΔH).

Acknowledgements

The reported study was funded by Russian Foundation for Basic Research, Government of Krasnoyarsk Territory, Krasnoyarsk Region Science and Technology Support Fund to the research projects No 16-48-242101/16 and No 03/16.

References

- 1 M. Sugimoto The Past, Present, and Future of Ferrites. J. of the American Ceramic Society. **82** (1999), 269. DOI: 10.1111/j.1551-2916.1999.tb20058.x.
- 2 R.H. Kodama, A.E. Berkowitz, E.J. McNiff Jr., S. Foner Surface spin disorder in NiFe2O4 nanoparticles. Physical Review Letters. **77** (1996), 394. DOI: /10.1103/PhysRevLett.77.394.
- 3 M. Sugimoto. Amorphous characteristics in spinel ferrites containing glassy oxides. JMMM.133 (1994). 460. DOI: 10.1016/0304-8853(94)90595-9.
- 4 A.C.F.M. Costa, E. Tortella, M.R. Morelli, R.H.G.A. Kiminami Synthesis, microstructure and magnetic properties of Ni-Zn ferrites. Journal of Magnetism and Magnetic Materials. **256** (2003), 174. DOI:10.1016/S0304-8853(02)00449-3.
- 5 A.V. Ushakov, I.V. Karpov, A.A. Lepeshev, M.I. Petrov Enhancing of magnetic flux pinning in YBa₂Cu₃O_{7-x}/CuO granular composite. J. Appl. Phys. **118** (2015), 023907. http://dx.doi.org/10.1063/1.4926549.
- 6 Ushakov, A.V. Specific Features of the Behavior of Electroarc CuO Nanoparticles in a Magnetic Field / A.V. Ushakov, I.V. Karpov, A.A. Lepeshev, M.I. Petrov, L.Yu. Fedorov // Physics of the Solid State. 2015. Vol. 57, No. 5, pp. 919–923. DOI: 10.1134/S1063783415050303.
- 7 Lepeshev, A. Modification of Structure and Physico-mechanical properties of Al-Cu-Fe Quasicrystal Alloy at Plasma Spraying / A. Lepeshev, D.J Soldelet, E. Rozhkova, A. Ushakov // Journal of Cluster Science. 2011. Vol. 22, No. 2, pp. 289-294. doi: 10.1007/s10876-011-0378-2.
- 8 Lepeshev, A.A. Modification of the Phase State and Structure of the Al–Cu–Fe Quasi-Crystalline Alloy during Plasma Deposition / A.A. Lepeshev, O.A. Bayukov, E.A. Rozhkova, I.V. Karpov, A.V. Ushakov, L.Yu. Fedorov // Physics of the Solid State. 2015. Vol. 57, No. 2, pp. 255–259. DOI: 10.1134/S1063783415020249.
- 9 Ushakov, A.V. Study of Magnetic Flux Pinning in Granular YBa₂Cu₃O_{7-y}/nanoZrO₂ Composites / A.V. Ushakov, I.V. Karpov, A.A. Lepeshev, M.I. Petorv, L.Yu. Fedorov // JETP Letters. 2014. Vol. 99, No. 2, pp. 99–103. DOI: 10.1134/S002136401402009X.
- 10 Lepeshev, A.A. Physical, Mechanical, and Tribological Properties of Quasicrystalline Al–Cu–Fe Coatings Prepared by Plasma Spraying / A.A. Lepeshev, E.A. Rozhkova, I.V. Karpov, A.V. Ushakov, L.Yu. Fedorov // Physics of the Solid State. 2013. Vol. 55, No. 12, pp. 2531–2536. DOI: 10.1134/S1063783413120202.
- 11 Lepeshev, A.A. Synthesis of Nanosized Titanium Oxide and Nitride Through Vacuum Arc Plasma Expansion Technique / A.A. Lepeshev, I.V. Karpov, A.V. Ushakov, L.Yu. Fedorov,

- A.A. Shaikhadinov // International Journal of Nanoscience. 2016. Vol. 15, No. 1-2, p. 1550027.
- 12 Lepeshev, A.A. The morphological and structural features of ferrite compositions (1–x)MeFe₂O₄·xP₂O₅ prepared by plasma spraying / A.A. Lepeshev, I.V. Karpov, A.V. Ushakov, G.E. Nagibin // Journal of Alloys and Compounds. 2016. Vol. 663, pp. 631-635. doi:10.1016/j.jallcom.2015.12.168
- 13 Ushakov, A.V. Plasmachemical Synthesis and Basic Properties of CoFe₂O₄ Magnetic Nanoparticles / A.V. Ushakov, I.V. Karpov, A.A. Lepeshev, L.Yu. Fedorov, A.A. Shaikhadinov // Technical Physics. 2016. Vol. 86, No. 1, pp. 103-107. doi: 10.1134/S1063784216010230
- 14 Lepeshev A. Amorphous and nanocrystalline materials of plasma spraying. Lambert Academic Publishing.-2015-10-28.-308 c.
 - 15 J.Smart. Effective field in magnetism theory. 1968. 271 p.